

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
15 May 2003 (15.05.2003)

PCT

(10) International Publication Number  
**WO 03/040270 A2**

(51) International Patent Classification<sup>7</sup>: **C10L 1/12**

(21) International Application Number: **PCT/GB02/05013**

(22) International Filing Date:  
6 November 2002 (06.11.2002)

(25) Filing Language: **English**

(26) Publication Language: **English**

(30) Priority Data:  
0126663.4 6 November 2001 (06.11.2001) **GB**

(71) Applicant (for all designated States except US): **OXON-ICA LIMITED** [GB/GB]; 7 Begbroke Science and Business Park, Sandy Lane, Yarnton, Kidlington, Oxford OX5 1PF (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **WAKEFIELD, Gareth** [GB/GB]; Oxonica Limited, 7 Begbroke Science and Business Park, Sandy Lane, Yarnton, Kidlington, Oxford OX5 1PF (GB).

(74) Agents: **ELLIS-JONES, Patrick, George, Armine** et al.; J.A. Kemp & CO., Gray's Inn, 14 South Square, London WC1R 5JJ (GB).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **CERIUM OXIDE NANOPARTICLES**

(57) Abstract: A fuel or fuel additives is disclosed which comprise particles of cerium oxide which have been doped with a divalent or trivalent metal or metalloid which is a rare earth metal, a transition metal or a metal of group IIA, IIIB, VB, or VIB of the Periodic Table.



**WO 03/040270 A2**

### CERIUM OXIDE NANOPARTICLES

5 This invention relates to cerium oxide nanoparticles which are useful as catalysts.

Cerium oxide is widely used as a catalyst in three way converters for the elimination of toxic exhaust emission gases in automobiles. The ceria contained within the catalyst can act as a chemically active component, working as an oxygen  
10 store by release of oxygen in the presence of reductive gases, and removal of oxygen by interaction with oxidising species.

Cerium oxide may store and release oxygen by the following processes:-



15

The key to the use of ceria for catalytic purposes is the low redox potential between the  $\text{Ce}^{3+}$  and  $\text{Ce}^{4+}$  ions (1.7V) that allows the above reaction to easily occur in exhaust gases. Cerium oxide may provide oxygen for the oxidation of CO or  $\text{C}_n\text{H}_n$  or may absorb oxygen for the reduction of  $\text{NO}_x$ . The amounts of oxygen reversibly  
20 provided in and removed from the gas phase are called the oxygen storage capacity (OSC) of ceria.

The above catalytic activity may occur when cerium oxide is added as an additive to fuel, for example diesel or petrol. However, in order for this effect to be useful the cerium oxide must be of a particle size small enough to remain in a stable  
25 dispersion in the fuel. The cerium oxide particles must be of a nanocrystalline nature, for example they should be less than 1 micron in size, and preferentially 1-300nm in size. In addition, as catalytic effects are surface area dependant the small particle size renders the nanocrystalline material more effective as a catalyst.

It has now been found, according to the present invention, that the catalytic  
30 efficiency of cerium oxide can be enhanced by addition of further components in the material. In particular it has been found that cerium oxide may be doped with

-2-

components that result in additional oxygen vacancies being formed. Thus doping will generally be substitution doping as opposed to interstitial doping. This will clearly enhance the OSC of the material, and hence its catalytic properties. Such dopant ions must be di- or tri-valent in order to provide oxygen vacancies. They must also be of a size that allows incorporation of the ion within the surface region of the cerium oxide nanoparticles. Accordingly metals with a large ionic radius should not be used. For example transition metals in the first and second row of transition metals are generally preferred over those listed in the third. The ceria serves as the oxygen activation and exchange medium during a redox reaction. However, because ceria and the like are ceramic materials, they have low electronic conductivity and low activity surface sites for the chemisorption of the reacting species. Transition metal additives are particularly useful to improve this situation. In addition, multivalent dopants will also have a catalytic effect of their own.

It is believed that doping in this way changes the zeta potential and thus improves the dispersion.

According to the present invention there is provided a fuel additive which comprises a particle of cerium oxide which has been doped with a divalent or trivalent metal or metalloid which is a rare earth metal, a transition metal, including a noble metal, or a metal of Group IIA, IIIB, VB, or VIB of the Periodic Table and a polar or non-polar organic solvent as well as a fuel containing such an additive or such particles. Typically the oxides will have the formula  $Ce_{1-x}M_xO_2$  where M is a said metal or metalloid, in particular Rh, Cu, Ag, Au, Pd, Pt, Sb, Se, Fe, Ga, Mg, Mn, Cr, Be, B, Co, V and Ca as well as Pr, Sm and Gd and x has a value up to 0.3, typically 0.01 or 0.1 to 0.2, or of the formula  $[(CeO_2)_{1-n}(REO_y)_n]_{1-k}M'_k$  where M' is a said metal or metalloid other than a rare earth, RE is a rare earth y is 1 or 1.5 and each of n and k, which may be the same or different, has a value up to 0.5, preferably up to 0.3, typically 0.01 or 0.1 to 0.2. Copper is particularly preferred. If too much dopant is used, there will be an increasing tendency for it to form an oxyanion thus negating the benefits of introducing it.

In general the particles will have a size not exceeding 1 micron and especially

-3-

not exceeding 300 nm, for example 1 to 300 nm, such as between 5 and 150 nm, in particular 10 to 50 nm, especially 10 to 20 nm.

Dopants may be incorporated into the cerium oxide nanoparticles principally by one of the following:-

- 5           i)       Doping within the particle during formation, e.g. by co-precipitation.
- ii)       Absorption of dopant ions onto the surface followed by firing of the dopant ion into the material. Note that particle size of the cerium oxide does not increase during firing.
- (iii)      A combustion synthesis. Doping during formation can be achieved by  
10   a combustion process whereby a mixture of salts of cerium and the dopant metal is heated together with, for example, glycine or other combustible solvent, preferably oxygen-containing, such as aliphatic alcohols, for example C<sub>1</sub> - C<sub>6</sub> alcohols, in particular isopropyl alcohol, in a flame to convert it to the oxide.
- (iv)      A mechano-chemical process typically involving milling, generally  
15   using a ball mill such as that described in WO99/59754 which involves subjecting a cerium oxide precursor and a dopant precursor in a non-reactive diluent to mechanical milling, heat treating the resulting material to convert it into the oxide and removing the diluent. The precursors are typically hydroxides, carbonates, sulphates or oxychlorides, especially cerium hydroxide and cerium carbonate. A  
20   typical diluent is sodium chloride which can readily be removed with water.
- (v)      A double decomposition process whereby, for example a salt of cerium and of the dopant, such as nitrate or chloride is reacted with a soluble oxide or hydroxide, for example of magnesium or calcium and the resulting oxide or hydroxide is recovered and the water soluble removed, typically by washing. In the  
25   case of the hydroxide, this is fired to convert it to the desired doped oxide.

Although it is clear that techniques other than (ii) will result in a dopant distribution that is even within the particle and the second may result in a predominately surface doping this is of little importance since the reaction involves surface based catalysis. The relative concentrations of dopant for optimum  
30   performance will vary however.

-4-

Of particular importance is the doping of copper into the cerium oxide nanoparticles. The redox properties of the copper-cerium system have been recognised as being synergistic, with the combination being more readily reduced than the corresponding independent compounds.

5        Doping during formation typically involves mixing, in an aqueous solution, a water-soluble cerium salt and a water-soluble salt of the dopant and raising the pH of the solution to cause the desired doped cerium oxide to precipitate.

      Suitable salts include nitrates and carbonates. The pH can be raised by the addition of an alkali such as ammonium hydroxide. A final pH exceeding 8,  
10 typically 8 to 10, is generally needed.

      As indicated, the dopant can also be inserted by firing. The dopant ion can be incorporated into the host lattice of cerium oxide by a baking technique typically at from 600°C to 1000°C. For this purpose cerium oxide and a salt of the metal dopant can be mixed in water and, if desired, ultrasonicated for, say, 10 minutes and boiled  
15 dry. The material is then fired, typically for several hours, for example 3 hours, to give the doped material.

      It will be appreciated that although reference is made to doping with a specific metal or metalloid, the metal or metalloid can be introduced as an oxide or, initially, a salt which is converted into an oxide during the process.

20        It will also be appreciated that, if desired, more than one dopant can be used. Likewise the cerium oxide can be in the form of a mixed oxide i.e. another tetravalent metal can be incorporated such as zirconium (or doped with both a rare earth and another metal or metalloid M').

      The amount of dopant incorporated can, of course, be adjusted by controlling  
25 the amount of doping salt employed, as one skilled in the art will appreciate.

      It is preferred that the particles are coated to prevent agglomeration. For this purpose the particles can be comminuted in an organic solvent in the presence of a coating agent which is an organic acid, anhydride or ester or a Lewis base. It has been found that, in this way which involves coating in situ, it is possible to  
30 significantly improve the coating of the oxide. Further, the resulting product can, in

-5-

many instances, be used directly without any intermediate step. Thus in some coating procedures it is necessary to dry the coated particles before dispersing them in a hydrocarbon solvent.

Thus the cerium oxide can be dispersible or soluble in the (liquid) fuel or  
5 another hydrocarbon or other solvent compatible with the fuel.

The particles which are subjected to the process should have as large a surface area as possible and preferably the particles have a surface area, before coating, of at least 10 m<sup>2</sup>/g and preferably a surface area of at least 50 or 75 m<sup>2</sup>/g, for example 80-150 m<sup>2</sup>/g, or 100-300m<sup>2</sup>/g.

10 The coating agent is suitably an organic acid, anhydride or ester or a Lewis base. The coating agent is preferably an organic carboxylic acid or an anhydride, typically one possessing at least 8 carbon atoms, for example 10 to 25 carbon atoms, especially 12 to 18 carbon atoms such as stearic acid. It will be appreciated that the carbon chain can be saturated or unsaturated, for example ethylenically unsaturated  
15 as in oleic acid. Similar comments apply to the anhydrides which can be used. A preferred anhydride is dodecylsuccinic anhydride. Other organic acids, anhydrides and esters which can be used in the process of the present invention include those derived from phosphoric acid and sulphonic acid. The esters are typically aliphatic esters, for example alkyl esters where both the acid and ester parts have 4 to 18  
20 carbon atoms.

Other coating or capping agents which can be used include Lewis bases which possess an aliphatic chain of at least 8 carbon atoms including mercapto compounds, phosphines, phosphine oxides and amines as well as long chain ethers, diols, esters and aldehydes. Polymeric materials including dendrimers can also be  
25 used provided that they possess a hydrophobic chain of at least 8 carbon atoms and one or more Lewis base groups, as well as mixtures of two or more such acids and/or Lewis bases.

Typical polar Lewis bases include trialkylphosphine oxides P(R<sup>3</sup>)<sub>3</sub>O, especially trioctylphosphine oxide (TOPO), trialkylphosphines, P(R<sup>3</sup>)<sub>3</sub>, amines  
30 N(R<sup>3</sup>)<sub>2</sub>, thiocompounds S(R<sup>3</sup>)<sub>2</sub> and carboxylic acids or esters R<sup>3</sup>COOR<sup>4</sup> and mixtures

-6-

thereof, wherein each  $R^3$ , which may be identical or different, is selected from  $C_{1-24}$  alkyl groups,  $C_{2-24}$  alkenyl groups, alkoxy groups of formula  $-O(C_{1-24} \text{ alkyl})$ , aryl groups and heterocyclic groups, with the proviso that at least one group  $R^3$  in each molecule is other than hydrogen; and wherein  $R^4$  is selected from hydrogen and  $C_{1-24}$  alkyl groups, preferably hydrogen and  $C_{1-4}$  alkyl groups. Typical examples of  $C_{1-24}$  and  $C_{1-4}$  alkyl groups,  $C_{2-24}$  alkenyl groups, aryl groups and heterocyclic groups are described below.

It is also possible to use as the polar Lewis base a polymer, including dendrimers, containing an electron rich group such as a polymer containing one or more of the moieties  $P(R^3)_3O$ ,  $P(R^3)_3$ ,  $N(R^3)_2$ ,  $S(R^3)_2$  or  $R^3COOR^4$  wherein  $R^3$  and  $R^4$  are as defined above; or a mixture of Lewis bases such as a mixture of two or more of the compounds or polymers mentioned above.

As used herein, a  $C_{1-4}$  alkyl group is an alkyl group as defined above which contains from 1 to 4 carbon atoms.  $C_{1-4}$  alkyl groups include methyl, ethyl, i-propyl, n-propyl, n-butyl and tert-butyl.

As used herein, a  $C_{2-24}$  alkenyl group is a linear or branched alkenyl group which may be unsubstituted or substituted at any position and which may contain heteroatoms selected from P, N, O and S. Typically, it is unsubstituted or carries one or two substituents. Suitable substituents include halogen, hydroxyl, cyano,  $-NR_2$ , nitro, oxo,  $-CO_2R$ ,  $-SOR$  and  $-SO_2R$  wherein each R may be identical or different and is selected from hydrogen or  $C_{1-4}$  alkyl.

As used herein, a  $C_{2-4}$  alkenyl group is an alkenyl group as defined above which contains from 2 to 4 carbon atoms.  $C_{2-4}$  alkenyl groups include ethenyl, propenyl and butenyl.

As used herein, an aryl group is typically a  $C_{6-10}$  aryl group such as phenyl or naphthyl, preferably phenyl. An aryl group may be unsubstituted or substituted at any position, with one or more substituent. Typically, it is unsubstituted or carries one or two substituent. Suitable substituent include  $C_{1-4}$  alkyl,  $C_{1-4}$  alkenyl, each of which may be substituted by one or more halogens, halogen, hydroxyl, cyano,  $-NR_2$ , nitro, oxo,  $-CO_2R$ ,  $-SOR$  and  $-SO_2R$  wherein each R may be identical or different and

-7-

is selected from hydrogen and C<sub>1-4</sub> alkyl.

As used herein, a heterocyclic group is a 5- to 10-membered ring containing one or more heteroatoms selected from N, O and S. Typical examples include pyridyl, pyrazinyl, pyrimidinyl, pyridazinyl, furanyl, thienyl, pyrazolidinyl, pyrrolyl  
5 and pyrazolyl groups. A heterocyclic group may be substituted or unsubstituted at any position, with one or more substituent. Typically, a heterocyclic group is unsubstituted or substituted by one or two substituents. Suitable substituents include C<sub>1-4</sub> alkyl, C<sub>1-4</sub> alkenyl, each of which may be substituted by one or more halogens, halogen, hydroxyl, cyano, -NR<sub>2</sub>, nitro, oxo, -CO<sub>2</sub>R, -SOR and -SO<sub>2</sub>R wherein each R  
10 may be identical or different and is selected from hydrogen and C<sub>1-4</sub> alkyl.

As used herein, halogen is fluorine, chlorine, bromine or iodine, preferably fluorine, chlorine or bromine.

The coating process can be carried out in an organic solvent. Preferably, the solvent is non-polar and is also preferably non-hydrophilic. It can be an aliphatic or  
15 an aromatic solvent. Typical examples include toluene, xylene, petrol, diesel fuel as well as heavier fuel oils. Naturally, the organic solvent used should be selected so that it is compatible with the intended end use of the coated particles. The presence of water should be avoided; the use of an anhydride as coating agent helps to eliminate any water present.

20 The coating process involves comminuting the particles so as to prevent any agglomerates from forming. The technique employed should be chosen so that the particles are adequately wetted by the agent and a degree of pressure or shear is desirable. Techniques which can be used for this purpose include high-speed stirring (e.g. at least 500 rpm) or tumbling, the use of a colloid mill, ultrasonics or ball  
25 milling. Ball milling is preferred. Typically, ball milling can be carried out in a pot where the larger the pot the larger the balls. By way of example, ceramic balls of 7 to 10 mm diameter are suitable when the milling takes place in a 1.25 litre pot. The time required will of course, be dependent on the nature of the particles but, generally, at least 4 hours is required. Good results can generally be obtained after  
30 24 hours so that the typical time is 12 to 36 hours.



-8-

The effectiveness of the process can be assessed by studying the stability of the resulting suspension. A turbidity procedure can be used to assess the extent to which the particles remain suspended and therefore un-agglomerated. The agglomerated particles will, of course fall out of suspension and therefore reduce the turbidity of the suspension. By way of example, it has been found that the addition of a suspension of cerium oxide particles obtained by the process is sufficient to act as a fuel catalyst when present in a concentration of about 4 ppm. This compares with a concentration of in excess of 40 ppm for an existing coated cerium oxide product.

10 The incorporation of the cerium oxide in fuel serves more than one purpose. The primary purpose is to act as a catalyst in the reduction of toxic exhaust gases on combustion of the fuel. However, it can serve another purpose in diesel engines. Diesel engines increasingly comprise a trap for particulates resulting from combustion of the diesel fuel. The presence of the cerium oxide in the traps helps to  
15 burn off the particulates which accumulate in the trap. Additionally organo platinum group metal compounds can be present as co-catalysts. Thus the fuels of the present invention can also comprise such a platinum group metal compound. These should be soluble in the fuel and include compounds of platinum or, for example, palladium and rhodium and mixtures of two or more thereof.

20 Suitable compounds include platinum acetylacetonate and compounds having the formula:  $X Pt R_1 R_2$  where X is a ligand containing at least one unsaturated carbon - carbon double bond which can be olefinic, acetylenic or aromatic and  $R_1$  and  $R_2$  are, independently, benzyl, phenyl, nitrobenzyl or alkyl of 1 to 10 carbon atoms such as diphenyl cyclooctadiene platinum (II). The use of the doped ceria enables  
25 one to use less of the organo platinum group metal than if undoped ceria is used and this represents an economic advantage.

If desired the resulting particles can be dried and re-dispersed in another organic solvent or in a polymer. Examples of suitable polymers include homo- and co-polymers of ethylene, propylene or styrene, and hydrocarbon-based elastomers  
30 such as those containing propylene, butadiene or isoprene.

-9-

The particles can be incorporated into the fuel directly or as an additive for the fuel. The particles are preferably incorporated into diesel fuel.

Typical additives which can be used in the fuel compositions, especially diesel fuel, include those conventionally used, such as:-

5       **Non polar organic solvents** such as aromatic and aliphatic hydrocarbons such as toluene, xylene and white spirit, e.g. those sold under the Trade Mark "SHELLSOL" by the Royal Dutch/Shell Group,

**Polar organic solvents**, in particular, alcohols generally aliphatic alcohols e.g. 2 ethylhexanol, decanol and isotridecanol,

10       **Detergents** such as hydrocarbyl-substituted amines and amides, e.g. hydrocarbyl-substituted succinimides, e.g. a polyisobutenyl succinimide,

**Dehazers**, e.g. alkoxylated phenol formaldehyde polymers such as those commercially available as "NALCO" (Trade Mark) 7D07 (ex Nalco) , and "TOLAD" (Trade Mark) 2683 (ex Petrolite),

15       **Anti-foaming agents** e.g. the polyether-modified polysiloxanes commercially available as "TEGOPREN" (Trade Mark) 5851 (ex Th. Goldschmidt) Q 25907 (ex Dow Corning) or "RHODORSIL" (Trade Mark) (ex Rhone Poulenc))

**Ignition improvers** such as aliphatic nitrates e.g. 2-ethylhexyl nitrate and cyclohexyl nitrate,

20       **Anti-rust agents** such as polyhydric alcohol esters of succinic acid derivatives (e.g. commercially sold by Rhein Chemie, Mannheim, Germany as "RC 4801", or by Ethyl corporation as HiTEC 536),

**Reodorants**,

25       **Anti-oxidants** e.g. phenolics such as 2,6-di-tert-butylphenol, or phenylenediamines such as N,N'-di-sec-butyl-p-phenylenediamine,

**Metal deactivators** such as salicylic acid derivatives, e.g. N, N'-disalicylidene-1,2-propane diamine and,

30       **Lubricity agents** such as fatty acids and esters, (e.g. those commercially available as EC831, P631, P633 or P639 (ex Infinium) or "HITEC" (Trade Mark) 580 (ex Ethyl Corporation), "Lubrizol" (trade mark) 539A (ex Lubrizol), "VECTRON"

-10-

(trade mark) 6010 (ex Shell Additives), OLI9000 (ex Associated Octel),

Unless otherwise stated, the (active matter) concentration of each additive in the fuel is generally up to 1000 ppmw (parts per million by weight of the diesel fuel), in particular up to 800 ppmw, e.g. 1 to 1000, 1 to 800 or 1-20, ppmw.

5       The (active matter) concentration of the dehazer in the diesel fuel is preferably in the range from 1 to 20ppmw. The (active matter) concentrations of other additives (with the exception of the detergent, ignition improver and the lubricity agent) are each preferably up to 20ppmw. The (active matter) concentration of the detergent is typically up to 800ppmw e.g. 10 to 500 ppmw. The (active matter)  
10 concentration of the ignition improver in the diesel fuel is preferably up to 600ppmw e.g. 100 to 250 ppmw. If a lubricity agent is incorporated into the diesel fuel, it is conveniently used in an amount of 100 to 500 ppmw.

Some of these additives are more commonly added directly at the refinery while the others form part of a diesel fuel additive (DFA), typically added at the point  
15 of loading with the tanker. A typical DFA comprises:

	detergent	10-70% (by weight)
	antirust	0-10%
	antifoam	0-10%
	dehazer	0-10%
20	non-polar solvent	0-50%
	polar solvent	0-40%

The diesel oil itself may be an additised (additive-containing) oil. If the diesel oil is an additised oil, it will contain minor amounts of one or more additives, e.g. anti-static agents, pipeline drag reducers, flow improvers, e.g. ethylene/vinyl  
25 acetate copolymers or acrylate/maleic anhydride copolymers, and wax anti-settling agents, e.g. those commercially available under the Trade Marks "PARAFLOW" (e.g. "PARAFLOW" 450; ex Paramins), "OCTEL" (e.g. "OCTEL" W 5000; ex Octel) and "DODIFLOW" (e.g. "DODIFLOW" V 3958; ex Hoechst).

The same or similar additives can be used for other fuels such as petrol, as  
30 one skilled in the art will appreciate.

-11-

The present invention also provides a method of improving the combustion of a fuel which comprises incorporating therein the cerium oxide particles.

-12-

CLAIMS

1. A fuel which comprises one or more particles of cerium oxide which have been doped with a divalent or trivalent metal or metalloid which is a rare earth metal, a transition metal or a metal of group IIA, IIIB, VB, or VIB of the Periodic Table.
2. A fuel additive which comprises one or more particles as defined in claim 1 and a polar or non-polar organic solvent.
3. A fuel or fuel additive according to claim 1 or 2 wherein the metal is a transition metal.
4. A fuel or fuel additive according to claim 3 wherein the metal is rhodium, copper, silver, gold, palladium, platinum, iron, manganese, chromium, cobalt or vanadium.
5. A fuel or fuel additive according to claim 1 or 2 wherein the metal is terbium, praseodymium, samarium, gadolinium, antimony, selenium, gallium, magnesium, beryllium, boron or calcium.
6. A fuel or fuel additive according to any one of the preceding claims wherein the oxide has the formula:
 
$$\text{Ce}_{1-x}\text{M}_x\text{O}_2$$
 where M is a said metal or metalloid and x has a value up to 0.3.
7. A fuel additive according to any one of the preceding claims wherein the oxide has the formula:
 
$$[(\text{CeO}_2)_{1-n}(\text{REO}_y)_n]_{1-k}\text{M}'_k$$
 where M' is a said metal or metalloid other than a rare earth, RE is a rare earth y is 1 or 1.5 and each of n and k, which may be the same or different, has a value up to 0.5.
8. A fuel or fuel additive according to any one of the preceding claims which has a size not exceeding 1 micron.
9. A fuel or fuel additive according to claim 8 which has a size from 1 to 300 nm.
10. A fuel or fuel additive according to any one of the preceding claims

-13-

wherein the cerium oxide has been doped with more than one said metal or metalloid and/or oxide thereof.

11. A fuel or fuel additive according to any one of the preceding claims which has been coated with an organic acid, anhydride or ester or a Lewis base.

5 12. A fuel or fuel additive according to claim 11 in which the coating agent is oleic acid or dodecylsuccinic anhydride.

13. A fuel according to any one of the preceding claims which is diesel fuel.

10 14. A fuel according to any one of the preceding claims which also comprises an organo platinum group compound.

15. A fuel additive according to any one of claims 1 to 12 wherein the solvent is an aliphatic or aromatic hydrocarbon or an aliphatic alcohol.

15 16. A fuel additive according to any one of claims 1 to 12 and 15 which comprises one or more of a detergent, dehazer, anti-foaming agent, ignition improver, anti-rust agent, reodorant, anti-oxidant, metal deactivator or lubricity agent.

17. Use of particles of cerium oxide as defined in any one of claims 1 to 12 as a fuel additive.

20 18. A method of improving the combustion of a fuel which comprises incorporating therein particles as defined in any one of claims 1 to 12.

19. A fuel which comprises a fuel additive as claimed in any one of claims 1 to 10, 15 and 16.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
15 May 2003 (15.05.2003)

PCT

(10) International Publication Number  
**WO 03/040270 A3**

(51) International Patent Classification<sup>7</sup>: **C10L 1/12**,  
1/10, C01F 17/00, C10L 10/02, 10/06

(21) International Application Number: PCT/GB02/05013

(22) International Filing Date:  
6 November 2002 (06.11.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0126663.4 6 November 2001 (06.11.2001) GB

(71) Applicant (for all designated States except US): **OXON-ICA LIMITED** [GB/GB]; 7 Begbroke Science and Business Park, Sandy Lane, Yarnton, Kidlington, Oxford OX5 1PF (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **WAKEFIELD, Gareth** [GB/GB]; Oxonica Limited, 7 Begbroke Science and Business Park, Sandy Lane, Yarnton, Kidlington, Oxford OX5 1PF (GB).

(74) Agents: **ELLIS-JONES, Patrick, George, Armine** et al.; J.A. Kemp & CO., Gray's Inn, 14 South Square, London WC1R 5JJ (GB).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(88) Date of publication of the international search report:  
4 December 2003

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: CERIUM OXIDE NANOPARTICLES

(57) Abstract: A fuel or fuel additives is disclosed which comprise particles of cerium oxide which have been doped with a divalent or trivalent metal or metalloid which is a rare earth metal, a transition metal or a metal of group IIA, IIIB, VB, or VIB of the Periodic Table.

WO 03/040270 A3

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/GB 02/05013

<b>A. CLASSIFICATION OF SUBJECT MATTER</b> IPC 7 C10L1/12 C10L1/10 C01F17/00 C10L10/02 C10L10/06		
According to International Patent Classification (IPC) or to both national classification and IPC		
<b>B. FIELDS SEARCHED</b> Minimum documentation searched (classification system followed by classification symbols) IPC 7 C10L		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used)		
<b>C. DOCUMENTS CONSIDERED TO BE RELEVANT</b>		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 01 10545 A (BLANCHARD GILBERT ; CHANE CHING JEAN YVES (FR); RHODIA TERRES RARES (F) 15 February 2001 (2001-02-15)	1-13, 15-19
Y	page 3, line 25 - page 4, line 35; claims 1-16; example 8	14
X	WO 97 19022 A (RHONE-POULENC CHIMIE) 29 May 1997 (1997-05-29)	1-6,8,9, 11-13, 15-19
	claims 3,4	
Y	WO 97 04045 A (CLEAN DIESEL TECHNOLOGIES) 6 February 1997 (1997-02-06)	14
	the whole document	
X	GB 1 452 783 A (KENT JAMES EISENTRAUT ET AL.) 13 October 1976 (1976-10-13)	7
	page 4, line 1 - line 6	
	----- -/-	
<input checked="" type="checkbox"/> Further documents are listed in the continuation of box C. <input checked="" type="checkbox"/> Patent family members are listed in annex.		
* Special categories of cited documents : *A* document defining the general state of the art which is not considered to be of particular relevance *E* earlier document but published on or after the international filing date *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) *O* document referring to an oral disclosure, use, exhibition or other means *P* document published prior to the international filing date but later than the priority date claimed *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art. *&* document member of the same patent family		
Date of the actual completion of the international search  3 October 2003		Date of mailing of the international search report  10/10/2003
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016		Authorized officer  De La Morinerie, B.



## INTERNATIONAL SEARCH REPORT

International Application No  
PCT/GB 02/05013

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 98 04655 A (DEN NESTE CORINNE VAN ; BRIARD GERARD (FR); BRISSET GUY (FR); PEYROT J) 5 February 1998 (1998-02-05) the whole document	10
A	WO 95 18198 A (RHONE-POULENC CHIMIE) 6 July 1995 (1995-07-06) claims 1-32	1-19
A	WO 99 13026 A (RHODIA CHIMIE) 18 March 1999 (1999-03-18) the whole document	1-19

# INTERNATIONAL SEARCH REPORT

Information on patent family members

Int: International Application No

PCT/GB 02/05013

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0110545	A	15-02-2001	FR 2797199 A1 BR 0012982 A CA 2387243 A1 CN 1374882 T EP 1210172 A1 WO 0110545 A1 JP 2003506529 T NO 20020553 A	09-02-2001 16-07-2002 15-02-2001 16-10-2002 05-06-2002 15-02-2001 18-02-2003 04-04-2002
WO 9719022	A	29-05-1997	FR 2741281 A1 AT 238239 T AU 7698996 A BR 9611637 A CA 2235716 A1 CN 1205678 A ,B DE 69627693 D1 EA 851 B1 EP 0862537 A1 WO 9719022 A1 HU 9903970 A2 JP 11501609 T NO 982295 A US 6136048 A	23-05-1997 15-05-2003 11-06-1997 06-04-1999 29-05-1997 20-01-1999 28-05-2003 26-06-2000 09-09-1998 29-05-1997 28-03-2000 09-02-1999 21-07-1998 24-10-2000
WO 9704045	A	06-02-1997	US 6003303 A AU 6548996 A CA 2227141 A1 EP 0854903 A1 WO 9704045 A1	21-12-1999 18-02-1997 06-02-1997 29-07-1998 06-02-1997
GB 1452783	A	13-10-1976	JP 50103505 A BE 809274 A1 CA 1016357 A1 US 3794473 A	15-08-1975 16-04-1974 30-08-1977 26-02-1974
WO 9804655	A	05-02-1998	FR 2751662 A1 AT 225388 T CN 1228802 A ,B DE 69716121 D1 DE 69716121 T2 EP 0946681 A1 ES 2183207 T3 WO 9804655 A1 JP 2000515917 T US 6096104 A	30-01-1998 15-10-2002 15-09-1999 07-11-2002 18-06-2003 06-10-1999 16-03-2003 05-02-1998 28-11-2000 01-08-2000
WO 9518198	A	06-07-1995	FR 2714717 A1 FR 2719081 A1 FR 2720405 A1 FR 2720441 A1 AU 1420595 A BR 9408456 A CN 1139951 A EP 0737236 A1 WO 9518198 A1 JP 9507278 T US 5813223 A	07-07-1995 27-10-1995 01-12-1995 01-12-1995 17-07-1995 05-08-1997 08-01-1997 16-10-1996 06-07-1995 22-07-1997 29-09-1998

Form PCT/ISA/210 (patent family annex) (July 1992)

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 02/05013

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9913026	A	18-03-1999	FR 2768155 A1 12-03-1999
			AU 9078898 A 29-03-1999
			BR 9812072 A 26-09-2000
			CA 2303137 A1 18-03-1999
			CN 1275158 T 29-11-2000
			EP 1019462 A1 19-07-2000
			WO 9913026 A1 18-03-1999
			HU 0004601 A2 28-04-2001
			JP 2001515946 T 25-09-2001
			NO 20001237 A 10-05-2000

Form PCT/ISA/210 (patent family annex) (July 1992)